
SPING PIO Water fed pole pump controller









Simple pole fitting radio remote

Switch from Wash to Rinse at the pole

Displays TDS reading and battery voltage

Unit is sealed to IP64, stopping water ingress

Easy to use and simple to install



A tried and tested design from pole-fed specialists, the Spring Pro has been developed with window cleaners in the field who know what they want from a window-cleaning product.

The use of a pump controller will give you exactly the right volume of water to the glass for a perfect clean, everytime.


Fit the simple three button remote to your pole and you have the control. Turn water ON/OFF or set flow to WASH (low flowrate) or RINSE (high flow rate) at the press of a button. It's that easy.

Dead end detection detects when water flow is restricted (i.e. when the pole has been disconnected from the hose) and safely shuts down the pump, reducing power and wear. Simply reconnect the pole and the pump will start up again.

Fine control of the flow rates means water control is exact, allowing you to work the way you want.

The three button interface is simple and intuitive to use. It also allows you to set your WASH flow and RINSE flow before starting work.

The battery voltage is available at the touch of a button. Advanced features will shut down the unit when the battery is too low, preventing irreversible battery damage.



Electrical Specification	Value	Mechanical Specification	Value
Supply Voltage	7-18V	Enclosure material	ABS
Maximum drive current	10A	Water resistance	IP64
Typical drive current	2-3A	Dimensions (mm)	115x65x40
Working temperature	-5 to 40C	Voltmeter accuracy	+/- 200mV